



STEAM GENERATORS

SG-08/SG-10

PRESSURE

4,5÷6
bar

STEAM FLOW RATE

75÷90
g/min

ABSORBED POWER

2÷3,2
kW

EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTIBUG
- ▶ AUTOMATIC SHUTDOWN
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ FLEX POWER
- ▶ DURABILITY



SG-08



SG-10
BOILER WITH AUTO FILLING TANK

MOST FREQUENTLY USE

AUTOMOTIVE



HO.RE.CA.



FOOD INDUSTRY AND RETAILERS



LARGE COMMON AREAS



SPECS



HANDLE FOR A CONVENIENT TRANSPORTATION



STAINLESS STEEL STRUCTURE SUITABLE FOR AREAS WHERE HYGENE IS A MUST



DIGITAL INDICATOR OF:
- BOILER TEMPERATURE
- STEAM READY
- WATER LACK

TECHNICAL DATA

		SG-8 S 4507 M	SG-10 S 5007 M	SG-10 S 6008 M
Code		GNVA40036	GNVA40037	GNVA40038
PERFORMANCE				
Operating pressure	bar/Mpa	4,5/0,45	5/05	6/0,6
Steam flow rate	g/min	~ 60-75	~ 65-80	~ 70-90
Max steam temperature	°C	150	155	160
Start up time	min	~ 9	~ 3	~ 2,5
Power supply	Ph-V-Hz	1-230/240-50/60	1-230/240-50/60	1-230/240-50/60
Max absorbed power	kW	2	2,2	3,2
Boiler volume	l	2	1,8 (continuous recharge)	1,8 (continuous recharge)
Water tank	l	-	2,5	2,5
Dimension (LxWxH)	cm	50x28x32	50x28x32	50x28x32
Weight	kg	6,5	7	8

STANDARD EQUIPMENT

CODE: IPIP40019
HANDGRIP + STEAM HOSE
2,5 m



CODE: MPVR40851
EXTENSION TUBE
L=500MM (2 PCS)



CODE: MPVR40852
NOZZLE JOINT



CODE: SPPV40052
GLASS CLEANER



CODE: SPPV40053
MULTIPURPOSE BRUSH



CODE: SPPV40054
TRIANGULAR BRUSH



CODE: SPPV40055
STEAM LANCE CURVED
L= 175



CODE: SPPV40056
SMALL ROUND BRUSH WITH
POLYESTER BRISTLES D.28



CODE: SPPV40057
SMALL ROUND BRUSH
WITH BRASS BRISTLES D.28



CODE: SPPV40058
RECTANGULAR CLOTH



OPTIONAL ACCESSORIES

CODE: MPVR40857
SELF REFFILING BOTTLE



CODE: AZMC40024
WRENCH FOR
MAINTENANCE



CODE: KTRI40446
TROLLEY

